

ORDER TOUCH SCREEN



32 43



1920 x 1080



350 Nits



Android 11



Touch Screen



8RAM+256GB



PANNEL

LCD size	32 / 43 inch
Light	LED
Max resolution	1920×1080(pixels)
Brightness(typ)/(min)	350cd/m²(typ.)
ContrastRatio(typ)/(min)	3000:1(typ.)
Response time(typ)/(min)	6ms(typ.)
pixel	0.2482mm×0.2482mm
HZ	60Hz
degree	178°(H)/178°(V)
life(typ)/(min)	30,000hrs(min.)

Android (stander)

view	941.2*529.4m
color	16.7M(8bit)
CPU	structure RK3568 Cotex-A55×4
GPU	2.0GHz
Internal cache capacity(RAM)	Quad-coreprocessor
Internal storage capacity (ROM)	Stander 2G (4G optional)
system(RAM)	Stander 16G (32G/64Goptional)
CUP connect	Android 11
	MIC-IN×1, RJ45×1, RS232×1, USB×4

PC Configuration (optional)

CPU(optional)	Intel J1900Quad-core processor/I3/I5/I7
HDD(optional)	64G SSD/128G SSD/256G SSD/512G SSD
RAM(optional)	4GB/8GB
WIFI	802.11b/g/n
Network card type	1Gigabit network card
Mother board interface	HDMI*1, VGA*1, RJ45*1,USB*4, LINE-OUT*1, MIC-IN*1

OUTSIDE

printer	80mm panel thermal printer
scanner	Support all common one-dimensional codes,two-dimensional codes
POS machine bracket	External POS machine bracket
Card reader(optional)	NFC card readerIC card reader
Camera(optional)	Monocular camera/binocular camera
Column(optional)	Metal column

Power supply

Voltage	100V~240V,50-60Hz
Max power	80W
Holding power	≤1W

Environment

Working temperature	0℃~50℃
Storage temperature	-20℃~60℃
Storage humidity	5%~90%RH
Working humidity	10%~90%RH

Structure

Size(W×H×D)	11942*665mm
weight	30KG
Weight with stand	48KG

Ouch data

Touch Specifications	Capacitive touch screen
Panel Size	32inch / 43inch
Product Structure	Glass / Glass
Number of Touch Points	10points
Resolution	25ppi(Min)
Operating Condition	-20℃~+70℃ at Min 45% to Max 85% RH
Storage Conditions	-30℃~+80℃ at Min 45% to Max 85% RH

Interface type

USB

Working voltage

DC+5V±5%

Communication type

USB2.0fullspeed

Average current

<400mA

Power supply mode

SingelUSBpowersupply

Consumption

<2.0W