

ORDER TOUCH SCREEN



32



1920 x 1080



360 Nits



Windows 10



Touch Screen



4RAM+64GB



LCD PANEL

LCD size
light source
resolution
brightness (min)
Contrast ratio (min)
reaction time (min)
Pixel pitch
Frame rate
Perspective
life (min)
visible area
Color saturation

32 inches
led Backlight
1920×1080 (pixels)
360 cd/m2
25 00:1
5 ms
0.3114 mm × 0.3114 mm
60Hz
178° (H)/178° (V)
30,000 hrs (min.)
698.4 mm × 392.85 mm
16. 7M (8bit)

CPU

Architecture
Working
GPU

RK3568 Cortex-A55X4
2. 0GHz
Quad-core

ANDROID CONFIGURATION (STANDARD)

Internal cache size (RAM)
Internal storage capacity
System version
Motherboard Interface

Standard configuration includes (2G / 4G)
Standard configuration: 16GB (32GB /64GB)
Windows 10
MIC-INX1, RJ45X1, RS232×1, USBX4

PERIPHERALS

printer
Scanner
POS machine stand
Card reader (optional)
Camera (optional)
Support column (optional)

80mm panel thermal printer
Supports automatic scanning of all common
Built-in POS machine bracket
NFC card reader/IC card reader
Monocular camera/Dual-lens camera
Metal pillars

POWER SUPPLY

Voltage
Maximum power
standby power

100V~240V, 50-60Hz
180W
≤ 1 W

TOUCH PARAMETERS

Touch
Panel size
Product Structure
Touch points
Total thickness
Product Hardness
Resolution
Working conditions
Storage conditions

Capacitive Touchscreen
32-inch
Glass/Glass
10 o'clock
3.3±0.3mm
6H
25 ppi (Min)
-20 C +70 C at Min 45% to Max 85% RH
-30 C +80 C at Min 45% to Max 85% RH

INTERFACE TYPE

USB

COMMUNICATION TYPE

USB 2.0 full speed

POWER SUPPLY METHOD

Single USB powered by

OPERATING VOLTAGE

DC+5V±5 %

AVERAGE CURRENT

< 400mA

POWER CONSUMPTION

<2. 0W