



6KW HQD
AIRCOOLING SPINDLE



HYBRID SERVO MOTOR
WITH REDUCER



A11DSP
CONTROLLER




DUST COLLECTOR




7.5KW INVERTER



MISTING SYSTEM



HIGH QUALITY
GUIDE RAILS



T-SLOT TABLE
VACCUM SYSTEM (OPTIONAL)



Industry Application



3D Wood



MDF



Aluminum



Acrylic



Forex



CNC
ENGRAVING



CNC
CUT



CNC
DESIGN



CNC
PROGRAM

Model	NAB-1325 N	Spindle Speed	0-18000RPM
Working area	1300 x 2500 x 200	Driver motors	Leadshine stepper
Table surface	T-Solt table	Inverter	7.5KW
X.Y transmission	Gear and Helical rack	Operating system	RICHAUTO A11
Z transmission	Ball Screw	Cooling system	Oil misting
XYZ Guide rail	High quality Guide rail	Working voltage	220V
Accuracy	0.02/2000mm	Software	ARTCUT/ARTCAM/TYPE 3
Max travel speed	25000mm/min	Weight	1000KG
Max working speed	15000mm/min	Machine Dimension	3100 x 1960 x 1750mm
Spindle power	6KW / HQD	Packing Dimension	3210 x 2070 x 1950mm

