

Specification Of Machine

- ✓ Fully Automatic Integrated Film Removing and Laminating; Dual-Power Anti-Deviation Rewinding.
- ✓ Suitable for AB film, Gold/Silver Lamination Effect, and Customized, and other applications. The Finished Printing has Higher Weather Resistance.
- ✓ Photorealistic 3D Visual Experience
- ✓ Independent White Ink Stirring Circulation Ink Supply System Static Elimination System without Ink Splashing
- ✓ International Top-level Accessories, Industrial Grade Quality
- ✓ Ink Shortage and Paper Shortage Alarm, Carriage Anti-Collision Truly Unattended.



Industry Application



CMYK Color Profile



Printer Model	DTF 0604				Media	Media Processing	Roll to Roll+Auto Feeding+Auto Roll Up		Protection Film Auto Peeling Off
Print Head Quantity	EPSON i3200 4 pcs					Media Heating	LED UV Lamp Curing		
Printing Width	60cm					Media Types	Outdoor Solvent / Eco-solvent Based Roll Media (Flex, Vinyl, Leather, Artificial Leather etc)		
Printing Speed 4H	Standard Mode	N/A	30m²/h	12m²/h		Operating System	WIN10 Professional 64Bit / WIN11		
	Production Mode	7m²/h	20m²/h	7m²/h	Power Supply	AC 220V, 50HZ±10%, UPS is required			
	High Resolution Mode	5m²/h	14m²/h	5m²/h	Power	1000W			
Ink Type	UV Ink: CMYK, LC, LM, LK, LLK, White, Varnish, Glue,Fluorescent M/Y				PC Configuration	CPU: INTEL i5/i7	RAM: 16G	SSD : 250G (For Disk C Only)	HD : 2TB Motherboard : ASUS
Image Format	TIFF,JPG,EPS,PDF				Temperature / Humidity	Temperature 20-30 °C Humidity 60-70%			
RIP Software	FLEXIPRINT (Overseas Standard) MAINTOP (Domestic Standard) / ONYX / CALDERA / PRINT FACTORY (Optional)				Packing Size L/W/H	2.00x1.35x0.79m			
Interface	USB 3.0/Gigabit Ethernet Port				G.W./N.W.	400kg/280kg			

