

## Specification Of Machine

- ✓ The printer features an innovative liftable rail beam design, allowing it to easily accommodate thicker materials.
- ✓ This adaptability makes it ideal for a wide range of printing applications, from traditional paper and cardboard to more robust substrates like wood, plastic, and metal.
- ✓ Designed for precision, this printer delivers high-resolution, delicate prints that capture even the finest details.
- ✓ Investing in this printer provides exceptional value, combining affordability with top-tier performance.
- ✓ Constructed with an industrial-grade configuration, this printer is built to last.
- ✓ Its robust design ensures stability during operation, reducing the risk of mechanical issues and downtime.


### Industry Application



Phone Case



KT Board



Signage



Acrylic



Bottle



CCD CAMERA  
(OPTIONAL)

### CMYK Color Profile



| Model              | NAB-9060                                                                         |                      |                      |
|--------------------|----------------------------------------------------------------------------------|----------------------|----------------------|
| Print Head         | EPSON I 3200 A1 / 4PCS + CCD                                                     |                      |                      |
| Color Mode         | 4C / 4C+W / 4C+W+V                                                               |                      |                      |
| Print Width        | 900mm x 600mm                                                                    |                      |                      |
| Print Mode         | FULL COLOR                                                                       | W+ C                 | W+ C+V               |
| PrintSpeed (sqm/h) | Standard Mode                                                                    | 18 m <sup>2</sup> /h | 27 m <sup>2</sup> /h |
|                    | Production Mode                                                                  | 12 m <sup>2</sup> /h | 18 m <sup>2</sup> /h |
|                    | High Resolution Mode                                                             | 6 m <sup>2</sup> /h  | 9 m <sup>2</sup> /h  |
| Media Type         | Glass , Acrylic , Wood , Ceramic , Metal Sheet , PVC Sheet , Plastic,3c product. |                      |                      |
| Media Thickness    | Max 120 mm                                                                       |                      |                      |
| Ink Type           | UV Curing ink                                                                    |                      |                      |

|                           |                                                                                                                         |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Special Ink               | Optional White ink or Varnish                                                                                           |
| File Format               | TIFF / PDF / JPES / EPS                                                                                                 |
| RIP                       | FLEXIPRINT(Standard) / CALDERA / ONYX / Print Factory (Optional)                                                        |
| Data Connector            | USB 3.0                                                                                                                 |
| Power                     | 220VAC(±10%) Single Phase 50/60 HZ                                                                                      |
| Power Consumption         | 3500 W                                                                                                                  |
| Machine Size/N.W.         | 225cm x 165cm x 152cm / 450 kg                                                                                          |
| Packing Size/G.W.         | 150cm x 225cm x 85cm                                                                                                    |
| Environmental Requirement | seperated , clean , low dust , well-ventilated , environmental , temperature : 20°C-28°C<br>relative humidity : 40%-60% |

