

FOLDING LED SCREEN P2.5



Pixel spacing
2.5 mm

Resolution ratio
128 x (h)64

Module Size
(w)320 x (h)160mm

Protective technology
GOB

Module weight
0.55kg

Dimension
646 x 2050 mm

Whole machine composition

machine module composition	(w)2 x (H)12
Overall resolution W * H	(w)256 x (H)768px
Display Size	640*1920mm
Dimension	646 x 2050 mm
Gross weight of the machine	43kg

parameters Optical

Flatness tolerance	0.5mm
White balanced brightness	650CD
Gray scale	14-16BT
Color temperature	3200-9000
Best visual distance	3-20M
Perspective (horizontal)	160°
Perspective (vertical)	160°
distance of luminous point	≤3%
luminance uniformity	≥95
Chromaticity uniformity	±0.003Cx,Cy
contrast ratio	8000:1

Power on requirements

Power supply requirements	110-240V
Peak power consumption	430W
Average Power	145W

Communication parameters

Synchronous/Asynchronous	support
Communication method	drive/Ethernet port/4G remote
Interface	JS485 - 1WIFI - 1U- 1HDMI2

Speaker

Is there a built-in speaker	50*12mm*2PCS
audio	3.5 Audio Interface/Supports External Amplifier

Performance processing

Drive mode	Constant current drive
Frame Frequency	60HZ
Refresh rate	≥3840HZ

Using parameters

Typical lifespan values	50000H
Working temperature range	- 40—50°C
Operating humidity range	10-80%
Storage Temperature Range	- 50—50RH
Storage humidity range	10-85%RH