

FOLDING LED SCREEN P2.5



Pixel spacing
2.5 mm

Resolution ratio
128 x (h)64

Module Size
(w)320 x (h)160mm

Protective technology
GOB

Module weight
0.55kg

Dimension
640x2070 / 1280x2070 mm

Whole machine composition	machine module composition	(w)4 x (H)12
	Overall resolution W * H	(w)512 x (H)768px
	Display Size	640*1920 / 1280*1920 mm
	Dimension	640 x 2070 / 1280 x 2070 mm
	Gross weight of the machine	80kg
parameters Optical	Flatness tolerance	0.5mm
	White balanced brightness	600CD
	Gray scale	14-16BT
	Color temperature	3200-9000
	Best visual distance	3-20M
	Perspective (horizontal)	160°
	Perspective (vertical)	160°
	distance of luminous point	≤3%
	luminance uniformity	≥95
	Chromaticity uniformity	±0.003Cx,Cy
Power on requirements	contrast ratio	8000:1
	Power supply requirements	100-240V
	Peak power consumption	850W
Communication parameters	Average Power	280W
	Synchronous/Asynchronous	support
	Communication method	drive/Ethernet port/4G remote
Speaker	Interface	JS485 - 1WIFI - 1U- 1HDMI2
	Is there a built-in speaker	50*12mm*2PCS
Performance processing	audio	Interface / Supports External Amplifier
	Drive mode	Constant current drive
	Frame Frequency	60HZ
Using parameters	Refresh rate	≥3840HZ
	Typical lifespan values	50000H
	Working temperature range	- 40—50°C
	Operating humidity range	10-80%
	Storage Temperature Range	- 50—50RH
	Storage humidity range	10-85%RH