

SEB-SLIM-1260 NAB LED Converter:

	ITEM	SEB-SLIM-1260
INPUT	VOLTAGE RANGE	AC200~240V
	FREQUENCY RANGE	50~60Hz
	EFFICIENCY(typ.)	92%
	AC CURRENT(typ.)	0.5A/220-240VAC
OUTPUT	DC VOLTAGE	12V
	RATED CURRENT	4.6ADC
	CONSUMPTION POWER	60W
	POWER FACTOR	PF ≥ 0.6
	LINE REGULATION	±5%
	LOAD REGULATION	±3%
PROTEC- TION	SHORT CIRCUIT	Work at 130~150% of rating Auto recovery
	OVER LOAD	Work at 120~140% of rating
	OVER TEMPERATURE	Active latch mode at case temperature 95
ISOLATION	WITHSTAND VOLTAGE	I/P-O/P : AC3.65KVAC , I/P-F.G : AC1.5KVAC , O/P-F.G : 0.5KVAC
ENVIRONMENT	WORKING TEMPRATURE	-20~50 , 80 , AT 80% load
OTHERS	DIMENSION/WEIGHT	138*38.6*26.7mm(L*W*H) / 0.25kg

SEB-SLIM-12100 NAB LED Converter:

	ITEM	SEB-SLIM-12100
INPUT	VOLTAGE RANGE	AC200~240V
	FREQUENCY RANGE	50~60Hz
	EFFICIENCY(typ.)	92%
	AC CURRENT(typ.)	0.76A/220-240VAC
OUTPUT	DC VOLTAGE	12V
	RATED CURRENT	7.6ADC
	CONSUMPTION POWER	100W
	POWER FACTOR	PF ≥ 0.6
	LINE REGULATION	±5%
	LOAD REGULATION	±3%
PROTEC- TION	SHORT CIRCUIT	Work at 130~150% of rating Auto recovery
	OVER LOAD	Work at 120~140% of rating
	OVER TEMPERATURE	Active latch mode at case temperature 95
ISOLATION	WITHSTAND VOLTAGE	I/P-O/P : AC3.65KVAC , I/P-F.G : AC1.5KVAC , O/P-F.G : 0.5KVAC
ENVIRONMENT	WORKING TEMPRATURE	-20~50 , 80 , AT 80% load
OTHERS	DIMENSION/WEIGHT	148*38.6*26.7mm(L*W*H) / 0.3kg

SEB-SLIM-12150 NAB LED Converter:

	ITEM	SEB-SLIM-12150
INPUT	VOLTAGE RANGE	AC200~240V
	FREQUENCY RANGE	50~60Hz
	EFFICIENCY(typ.)	92%
	AC CURRENT(typ.)	1.1A/220-240VAC
OUTPUT	DC VOLTAGE	12V
	RATED CURRENT	11.3ADC
	CONSUMPTION POWER	150W
	POWER FACTOR	PF ≥ 0.6
	LINE REGULATION	±5%
	LOAD REGULATION	±3%
PROTEC- TION	SHORT CIRCUIT	Work at 130~150% of rating Auto recovery
	OVER LOAD	Work at 120~140% of rating
	OVER TEMPERATURE	Active latch mode at case temperature 95
ISOLATION	WITHSTAND VOLTAGE	I/P-O/P : AC3.65KVAC , I/P-F.G : AC1.5KVAC , O/P-F.G : 0.5KVAC
ENVIRONMENT	WORKING TEMPRATURE	-20~50 , 80 , AT 80% load
OTHERS	DIMENSION/WEIGHT	123*50.7*35mm(L*W*H) / 0.4kg

SEB-SLIM-12200 NAB LED Converter:

	ITEM	SEB-SLIM-12200
INPUT	VOLTAGE RANGE	AC200~240V
	FREQUENCY RANGE	50~60Hz
	EFFICIENCY(typ.)	92%
	AC CURRENT(typ.)	1.4A/220-240VAC
	DC VOLTAGE	12V
	RATED CURRENT	16ADC
OUTPUT	CONSUMPTION POWER	200W
	POWER FACTOR	PF ≥ 0.6
	LINE REGULATION	±5%
	LOAD REGULATION	±3%
PROTEC- TION	SHORT CIRCUIT	Work at 130~150% of rating Auto recovery
	OVER LOAD	Work at 120~140% of rating
	OVER TEMPERATURE	Active latch mode at case temperature 95
ISOLATION	WITHSTAND VOLTAGE	I/P-O/P : AC3.65KVAC , I/P-F.G : AC1.5KVAC , O/P-F.G : 0.5KVAC
ENVIRONMENT	WORKING TEMPRATURE	-20~50 , 80 , AT 80% load
OTHERS	DIMENSION/WEIGHT	141*50.7*35mm(L*W*H) / 0.43kg

SEB-SLIM-12300 NAB LED Converter:

	ITEM	SEB-SLIM-12300
INPUT	VOLTAGE RANGE	AC200~240V
	FREQUENCY RANGE	50~60Hz
	EFFICIENCY(typ.)	92%
	AC CURRENT(typ.)	2.3A/220-240VAC
OUTPUT	DC VOLTAGE	12V
	RATED CURRENT	23ADC
	CONSUMPTION POWER	300W
	POWER FACTOR	PF ≥ 0.6
	LINE REGULATION	±5%
	LOAD REGULATION	±3%
PROTEC- TION	SHORT CIRCUIT	Work at 130~150% of rating Auto recovery
	OVER LOAD	Work at 120~140% of rating
	OVER TEMPERATURE	Active latch mode at case temperature 95
ISOLATION	WITHSTAND VOLTAGE	I/P-O/P : AC3.65KVAC , I/P-F.G : AC1.5KVAC , O/P-F.G : 0.5KVAC
OTHERS	DIMENSION/WEIGHT	171*50.7*35mm(L*W*H) / 0.53kg