

SEB-SLIM-2460 NAB LED Converter:

ITEM		SBE-2460
INPUT	VOLTAGE RANGE	AC200~240V
	FREQUENCY RANGE	50~60Hz
	EFFICIENCY(typ.)	92%
	AC CURRENT(typ.)	0.5A/220-240VAC
OUTPUT	DC VOLTAGE	24V
	RATED CURRENT	3.2A
	CONSUMPTION POWER	60W
	POWER FACTOR	PF ≥ 0.6
	LINE REGULATION	±5%
	LOAD REGULATION	±3%
PROTECTION	SHORT CIRCUIT	Work at 130~150% of rating Auto recovery
	OVER LOAD	Work at 120~140% of rating
	OVER TEMPERATURE	Active latch mode at case temperature 95
ISOLATION	WITHSTAND VOLTAGE	I/P-O/P : AC3.65KVAC , I/P-F.G : AC1.5KVAC , O/P-F.G : 0.5KVAC
ENVIRONMENT	WORKING TEMPRATURE	-20~50 , 80 , AT 80% load
OTHERS	DIMENSION/WEIGHT	138*38.6*26.7mm(L*W*H) / 0.25kg

SEB-SLIM-24100 NAB LED Converter:

ITEM	SBE-24100
INPUT	VOLTAGE RANGE
	AC200~240V
	FREQUENCY RANGE
	50~60Hz
OUTPUT	EFFICIENCY(typ.)
	92%
	AC CURRENT(typ.)
	0.76A/220-240VAC
PROTEC- TION	DC VOLTAGE
	24V
	RATED CURRENT
	3.8A
	CONSUMPTION POWER
	100W
ISOLATION	POWER FACTOR
	PF ≥ 0.6
	LINE REGULATION
ENVIRONMEN T	±5%
	LOAD REGULATION
	±3%
OTHERS	SHORT CIRCUIT
	Work at 130~150% of rating Auto recovery
	OVER LOAD
	Work at 120~140% of rating
	OVER TEMPERATURE
	Active latch mode at case temperature 95
	WITHSTAND VOLTAGE
	I/P-O/P : AC3.65KVAC , I/P-F.G : AC1.5KVAC , O/P-F.G : 0.5KVAC
	WORKING TEMPRATURE
	-20~50 , 80 , AT 80% load
	DIMENSION/WEIGHT
	148*38.6*26.7mm(L*W*H) / 0.3kg

SEB-SLIM-24150 NAB LED Converter:

ITEM		SBE-24150
INPUT	VOLTAGE RANGE	AC200~240V
	FREQUENCY RANGE	50~60Hz
	EFFICIENCY(typ.)	92%
	AC CURRENT(typ.)	1.1A/220-240VAC
OUTPUT	DC VOLTAGE	24V
	RATED CURRENT	5.65A
	CONSUMPTION POWER	150W
	POWER FACTOR	PF ≥ 0.6
	LINE REGULATION	±5%
	LOAD REGULATION	±3%
PROTEC-TION	SHORT CIRCUIT	Work at 130~150% of rating Auto recovery
	OVER LOAD	Work at 120~140% of rating
	OVER TEMPERATURE	Active latch mode at case temperature 95
ISOLATION	WITHSTAND VOLTAGE	I/P-O/P : AC3.65KVAC , I/P-F.G : AC1.5KVAC , O/P-F.G : 0.5KVAC
ENVIRONMENT	WORKING TEMPRATURE	-20~50 , 80 , AT 80% load
OTHERS	DIMENSION/WEIGHT	123*50.7*35mm(L*W*H) / 0.4kg

SEB-SLIM-24200 NAB LED Converter:

ITEM		SBE-24200
INPUT	VOLTAGE RANGE	AC200~240V
	FREQUENCY RANGE	50~60Hz
	EFFICIENCY(typ.)	92%
	AC CURRENT(typ.)	1.4A/220-240VAC
OUTPUT	DC VOLTAGE	24V
	RATED CURRENT	8A
	CONSUMPTION POWER	200W
	POWER FACTOR	PF ≥ 0.6
	LINE REGULATION	±5%
	LOAD REGULATION	±3%
PROTEC- TION	SHORT CIRCUIT	Work at 130~150% of rating Auto recovery
	OVER LOAD	Work at 120~140% of rating
	OVER TEMPERATURE	Active latch mode at case temperature 95
ISOLATION	WITHSTAND VOLTAGE	I/P-O/P : AC3.65KVAC , I/P-F.G : AC1.5KVAC , O/P-F.G : 0.5KVAC
ENVIRONMENT	WORKING TEMPRATURE	-20~50 , 80 , AT 80% load
OTHERS	DIMENSION/WEIGHT	141*50.7*35mm(L*W*H) / 0.43kg

SEB-SLIM-24300 NAB LED Converter:

ITEM		SBE-24300
INPUT	VOLTAGE RANGE	AC200~240V
	FREQUENCY RANGE	50~60Hz
	EFFICIENCY(typ.)	92%
	AC CURRENT(typ.)	2.3A/220-240VAC
OUTPUT	DC VOLTAGE	24V
	RATED CURRENT	11.5A
	CONSUMPTION POWER	300W
	POWER FACTOR	PF ≥ 0.6
	LINE REGULATION	±5%
	LOAD REGULATION	±3%
PROTEC- TION	SHORT CIRCUIT	Work at 130~150% of rating Auto recovery
	OVER LOAD	Work at 120~140% of rating
	OVER TEMPERATURE	Active latch mode at case temperature 95
ISOLATION	WITHSTAND VOLTAGE	I/P-O/P : AC3.65KVAC , I/P-F.G : AC1.5KVAC , O/P-F.G : 0.5KVAC
OTHERS	DIMENSION/WEIGHT	171*50.7*35mm(L*W*H) / 0.53kg